Date July 25, 2018

To Town of Cumberland Planning Board

From Carla Nixon, Town Planner

Subject Minor Staff Site Plan Review MSAD # 51

## 1. REQUEST/PROJECT DESCRIPTION:

The applicant is MSAD # 51. Scott Poulin, Director of Finance, Human Resources and Operations for the MSAD, is the representative. The applicant is proposing to construct a 15' x 20' (300 sf) 1 story, unheated building to be used as a storage shed. The parcel is shown on Cumberland Tax Assessor's Map U-11, Lot 1.

The use, classified as an Accessory Building to a Municipal Use is a permitted use in the Medium Density Residential (MDR) zoning district.

This project is subject to review under the provisions of the Minor Staff Site Plan Review Ordinance as it involves the construction of a new structure that is less than 1,000 square feet.

## 2. PROJECT HISTORY: None

#### 3. DESCRIPTION:

**Proposed Use:** Storage Shed on skids

**Employees:** N/A **Parking:** N/A

Water: No water required. Sewer/Septic: No septic required. Electrical: None required

**Floodplain:** Map # 230162 0015B - Designation: Zone C (area of

minimal flooding)

**Fire Protection:** Hydrant on Main Street

Lighting: None proposed.
Solid Waste Disposal: None Required

4. Outside Agency Approvals: None required

5. Town Planner's Review: See Findings of Fact

**6.** Town Engineer's Review: None required.

7. Section 229-4: Waivers and modifications. Where the Planning Board or Town Planner finds that there are special circumstances of a particular plan that make a particular submission requirement or standard inapplicable, a waiver may be granted, provided that such waiver will not have the effect of nullifying the intent and purpose of the Comprehensive Plan. The applicant shall submit, in writing, the reason for the

requested waiver. In granting waivers or modifications, the Planning Board or Town Planner may require such conditions that will substantially secure the objectives of the standards so waived or modified.

Waiver Requests: There are no waiver requests.

\_\_\_\_\_\_

# **Chapter 229 – SITE PLAN REVIEW**

### SECTION 10: APPROVAL STANDARDS AND CRITERIA

The following criteria shall be used by the Planning Board in reviewing applications for site plan review and shall serve as minimum requirements for approval of the application. The application shall be approved unless the Planning Board determines that the applicant has failed to meet one or more of these standards. In all instances, the burden of proof shall be on the applicant who must produce evidence sufficient to warrant a finding that all applicable criteria have been met.

## Chapter 229 - Site Plan Review, Section 10: Approval Standards and Criteria

The following criteria shall be used by the Planning Board in reviewing applications for site plan review and shall serve as minimum requirements for approval of the application. The application shall be approved unless the Planning Board determines that the applicant has failed to meet one or more of these standards. In all instances, the burden of proof shall be on the applicant who must produce evidence sufficient to warrant a finding that all applicable criteria have been met.

**A. Utilization of the Site:** Utilization of the Site - The plan for the development, including buildings, lots, and support facilities, must reflect the natural capabilities of the site to support development. Environmentally sensitive areas, including but not limited to, wetlands, steep slopes, floodplains, significant wildlife habitats, fisheries, scenic areas, habitat for rare and endangered plants and animals, unique natural communities and natural areas, and sand and gravel aquifers must be maintained and preserved to the maximum extent. The development must include appropriate measures for protecting these resources, including but not limited to, modification of the proposed design of the site, timing of construction, and limiting the extent of excavation.

The placement of a 300 sf shed (on skids) on the MSAD's campus will not affect any environmentally sensitive areas.

Based on the above findings of fact, the Town Planner finds the standards of this section have been met.

### B. Traffic, Circulation and Parking

(1) Traffic Access and Parking. Vehicular access to and from the development must be safe and convenient.

- (a) Any driveway or proposed street must be designed so as to provide the minimum sight distance according to the Maine Department of Transportation standards, to the maximum extent possible.
- **(b)** Points of access and egress must be located to avoid hazardous conflicts with existing turning movements and traffic flows.
- (c) The grade of any proposed drive or street must be not more than + 3% for a minimum of two (2) car lengths, or forty (40) feet, from the intersection.
- (d) The intersection of any access/egress drive or proposed street must function: (a) at a Level of Service D, or better, following development if the project will generate one thousand (1,000) or more vehicle trips per twenty-four (24) hour period; or (b) at a level which will allow safe access into and out of the project if less than one thousand (1,000) trips are generated.
- **(e)** Where a lot has frontage on two (2) or more streets, the primary access to and egress from the lot must be provided from the street where there is less potential for traffic congestion and for traffic and pedestrians hazards. Access from other streets may be allowed if it is safe and does not promote short cutting through the site.
- (f) Where it is necessary to safeguard against hazards to traffic and pedestrians and/ or to avoid traffic congestion, the applicant shall be responsible for providing turning lanes, traffic directional islands, and traffic controls within public streets.
- **(g)** Access ways must be designed and have sufficient capacity to avoid queuing of entering vehicles on any public street.
- **(h)** The following criteria must be used to limit the number of driveways serving a proposed project:
- (1) No use which generates less than one hundred (100) vehicle trips per day shall have more than one (1) two-way driveway onto a single roadway. Such driveway must be no greater than thirty (30) feet wide.
- (2) No use which generates one hundred (100) or more vehicle trips per day shall have more than two (2) points of entry from and two (2) points of egress to a single roadway. The combined width of all access ways must not exceed sixty (60) feet.

## (2) Access way Location and Spacing

Access ways must meet the following standards:

- (a) Private entrance / exits must be located at least fifty (50) feet from the closest un-signalized intersection and one hundred fifty (150) feet from the closest signalized intersection, as measured from the point of tangency for the corner to the point of tangency for the access way. This requirement may be reduced if the shape of the site does not allow conformance with this standard.
- **(b)** Private access ways in or out of a development must be separated by a minimum of seventy-five (75) feet where possible.
- **(3) Internal Vehicular Circulation.** The layout of the site must provide for the safe movement of passenger, service, and emergency vehicles through the site.
- (a) Projects that will be served by delivery vehicles must provide a clear route for such vehicles with appropriate geometric design to allow turning and backing.
- **(b)** Clear routes of access must be provided and maintained for emergency vehicles to and around buildings and must be posted with appropriate signage (fire lane no parking).
- **(c)** The layout and design of parking areas must provide for safe and convenient circulation of vehicles throughout the lot.
- (d) All roadways must be designed to harmonize with the topographic and natural features of the site insofar as practical by minimizing filling, grading, excavation, or other similar activities which result in unstable soil conditions and soil erosion, by fitting the development to the natural contour of the land and avoiding substantial areas of excessive grade and tree removal, and by retaining existing vegetation during construction. The road network must provide for vehicular,

pedestrian, and cyclist safety, all season emergency access, snow storage, and delivery and collection services.

- (4) Parking Layout and Design. Off street parking must conform to the following standards:
- (a) Parking areas with more than two (2) parking spaces must be arranged so that it is not necessary for vehicles to back into the street.
- **(b)** All parking spaces, access drives, and impervious surfaces must be located at least fifteen (15) feet from any side or rear lot line, except where standards for buffer yards require a greater distance. No parking spaces or asphalt type surface shall be located within fifteen (15) feet of the front property line. Parking lots on adjoining lots may be connected by accessways not exceeding twenty-four (24) feet in width.
- (c) Parking stalls and aisle layout must conform to the following standards.

Parking Angle	Stall Width	Skew Width	Stall Depth Width	Aisle
90°	9'-0"		18'-0"	24'-0" 2-way
60°	8'-6"	10'-6"	18'-0"	16'-0" 1-way
45°	8'-6"	12'-9"	17'-6"	12'-0" 1-way
30°	8'-6"	17'-0"	17'-0"	12'-0" 1 way

- **(d)** In lots utilizing diagonal parking, the direction of proper traffic flow must be indicated by signs, pavement markings or other permanent indications and maintained as necessary.
- **(e)** Parking areas must be designed to permit each motor vehicle to proceed to and from the parking space provided for it without requiring the moving of any other motor vehicles.
- (f) Provisions must be made to restrict the "overhang" of parked vehicles when it might restrict traffic flow on adjacent through roads, restrict pedestrian or bicycle movement on adjacent walkways, or damage landscape materials.

# (5) Building and Parking Placement

- (a) The site design should avoid creating a building surrounded by a parking lot. Parking should be to the side and preferably in the back. In rural, uncongested areas buildings should be set well back from the road so as to conform to the rural character of the area. If the parking is in front, a generous, landscaped buffer between road and parking lot is to be provided. Unused areas should be kept natural, as field, forest, wetland, etc.
- **(b)** Where two or more buildings are proposed, the buildings should be grouped and linked with sidewalks; tree planting should be used to provide shade and break up the scale of the site. Parking areas should be separated from the building by a minimum of five (5) to ten (10) feet. Plantings should be provided along the building edge, particularly where building facades consist of long or unbroken walls.
- **(6) Pedestrian Circulation:** The site plan must provide for a system of pedestrian ways within the development appropriate to the type and scale of development. This system must connect the major building entrances/ exits with parking areas and with existing sidewalks, if they exist or are planned in the vicinity of the project. The pedestrian network may be located either in the street right-of-way or outside of the right-of-way in open space or recreation areas. The system must be designed to link the project with residential, recreational, and commercial facilities, schools, bus stops, and existing sidewalks in the neighborhood or, when appropriate, to connect the amenities such as parks or open space on or adjacent to the site.

There are no proposed changes to the site circulation or parking involved in this project.

Based on the above findings of fact, the Town Planner finds the standards of this section have been met.

## C. Stormwater Management and Erosion Control

- (1) Stormwater Management. Adequate provisions must be made for the collection and disposal of all stormwater that runs off proposed streets, parking areas, roofs, and other surfaces, through a stormwater drainage system and maintenance plan, which must not have adverse impacts on abutting or downstream properties.
- (a) To the extent possible, the plan must retain stormwater on the site using the natural features of the site.
- **(b)** Unless the discharge is directly to the ocean or major river segment, stormwater runoff systems must detain or retain water such that the rate of flow from the site after development does not exceed the predevelopment rate.
- **(c)** The applicant must demonstrate that on and off-site downstream channel or system capacity is sufficient to carry the flow without adverse effects, including but not limited to, flooding and erosion of shoreland areas, or that he / she will be responsible for whatever improvements are needed to provide the required increase in capacity and / or mitigation.
- (d) All natural drainage ways must be preserved at their natural gradients and must not be filled or converted to a closed system unless approved as part of the site plan review.
- **(e)** The design of the stormwater drainage system must provide for the disposal of stormwater without damage to streets, adjacent properties, downstream properties, soils, and vegetation.
- **(f)** The design of the storm drainage systems must be fully cognizant of upstream runoff which must pass over or through the site to be developed and provide for this movement.
- (g) The biological and chemical properties of the receiving waters must not be degraded by the stormwater runoff from the development site. The use of oil and grease traps in manholes, the use of on-site vegetated waterways, and vegetated buffer strips along waterways and drainage swales, and the reduction in use of deicing salts and fertilizers may be required, especially where the development stormwater discharges into a gravel aquifer area or other water supply source, or a great pond.

# (2) Erosion Control

- (a) All building, site, and roadway designs and layouts must harmonize with existing topography and conserve desirable natural surroundings to the fullest extent possible, such that filling, excavation and earth moving activity must be kept to a minimum. Parking lots on sloped sites must be terraced to avoid undue cut and fill, and / or the need for retaining walls. Natural vegetation must be preserved and protected wherever possible.
- **(b)** Soil erosion and sedimentation of watercourses and water bodies must be minimized by an active program meeting the requirements of the Maine Erosion and Sediment Control Handbook for Construction: Best Management Practices, dated March 1991, and as amended from time to time.

A building permit will be required and any erosion control measures will be inspected by the CEO. The removal of an older shed and replacement with this new shed on skids will not increase the amount of stormwater on the site.

Based on the above findings of fact, the Town Planner finds the standards of this section have been met.

#### (D) Water, Sewer, and Fire Protection

(1) Water Supply Provisions: The development must be provided with a system of water supply that provides each use with an adequate supply of water. If the project is to be served by a public water supply, the applicant must secure and submit a written statement from the supplier that the proposed water supply system conforms with its design and construction

standards, will not result in an undue burden on the source of distribution system, and will be installed in a manner adequate to provide needed domestic and fire protection flows.

- **(2) Sewage Disposal Provisions:** The development must be provided with a method of disposing of sewage which is in compliance with the State Plumbing Code. If provisions are proposed for on-site waste disposal, all such systems must conform to the Subsurface Wastewater Disposal Rules.
- **(3) Utilities:** The development must be provided with electrical, telephone, and telecommunication service adequate to meet the anticipated use of the project. New utility lines and facilities must be screened from view to the extent feasible. If the service in the street or on adjoining lots is underground, the new service must be placed underground.
- **(4) Fire Protection:** The site design must comply with the Fire Protection Ordinance. The Fire Chief shall issue the applicant a "Certificate of Compliance" once the applicant has met the design requirement of the Town's Fire Protection Ordinance.

The proposed shed does not include water or sewer service. Fire protection is not required for the unheated shed.

Based on the above findings of fact, the Town Planner finds the standards of this section have been met.

#### E. Water Protection

(1) **Groundwater Protection**: The proposed site development and use must not adversely impact either the quality or quantity of groundwater available to abutting properties or to the public water supply systems. Applicants whose projects involve on-site water supply or sewage disposal systems with a capacity of two thousand (2,000) gallons per day or greater must demonstrate that the groundwater at the property line will comply, following development, with the standards for safe drinking water as established by the State of Maine.

There will be no septic systems needed for this project.

- (2) Water Quality: All aspects of the project must be designed so that:
- (a) No person shall locate, store, discharge, or permit the discharge of any treated, untreated, or inadequately treated liquid, gaseous, or solid materials of such nature, quantity, obnoxious, toxicity, or temperature that may run off, seep, percolate, or wash into surface or groundwaters so as to contaminate, pollute, or harm such waters or cause nuisances, such as objectionable shore deposits, floating or submerged debris, oil or scum, color, odor, taste, or unsightliness or be harmful to human, animal, plant, or aquatic life.
- **(b)** All storage facilities for fuel, chemicals, chemical or industrial wastes, and biodegradable raw materials, must meet the standards of the Maine Department of Environmental Protection and the State Fire Marshall's Office.

There will be no storage facilities for fuel, chemicals, chemical or industrial wastes or biodegradable raw materials. Nor will there be any discharge of liquid, gaseous or solid materials.

(3) Aquifer Protection: If the site is located within the Town Aquifer Protection Area, a positive finding by the Board that the proposed plan will not adversely affect the aquifer is required. The site is located within the Town Aquifer Protection Area.

Based on the materials included in the application, the Town Planner finds that the standards of this section have been met.

**F. Floodplain Management:** If any portion of the site is located within a special flood hazard area as identified by the Federal Emergency Management Agency, all use and development of that portion of the site must be consistent with the Town's Floodplain management provisions.

The site is not located within a floodplain.

Based on the above finding of fact, the Town Planner finds the standards of this section have been met.

**G. Historic and Archaeological Resources:** If any portion of the site has been identified as containing historic or archaeological resources, the development must include appropriate measures for protecting these resources, including but not limited to, modification of the proposed design of the site, timing of construction, and limiting the extent of excavation.

There are letters on file from previous site plan applications) stating that the Maine Historic Preservation Commission has not found there to be any historical or archaeological resources present on the site of the school campus.

Based on the above finding of fact, the Town Planner finds the standards of this section have been met.

## H. Exterior Lighting:

The proposed development must have adequate exterior lighting to provide for its safe use during nighttime hours, if such use is contemplated. All exterior lighting must be designed and shielded to avoid undue glare, adverse impact on neighboring properties and rights - of way, and the unnecessary lighting of the night sky.

No exterior lighting is proposed.

Based on the above findings of fact, the Town Planner finds the standards of this section have been met.

#### I. Buffering and Landscaping

- (1) Buffering of Adjacent Uses: The development must provide for the buffering of adjacent uses where there is a transition from one type of use to another use and for the screening of mechanical equipment and service and storage areas. The buffer may be provided by distance, landscaping, fencing, changes in grade, and / or a combination of these or other techniques.
- **(2) Landscaping:** Landscaping must be provided as part of site design. The landscape plan for the entire site must use landscape materials to integrate the various elements on site, preserve and enhance the particular identity of the site, and create a pleasing site character. The landscaping should define street edges, break up parking areas, soften the appearance of the development, and protect abutting properties.

The proposed shed will not have an impact of adjacent properties due to its distance from residences adjacent to the campus.

Based on the above findings of fact, the Town Planner finds the standards of this section have been met.

**J. Noise:** The development must control noise levels such that it will not create a nuisance for neighboring properties.

The shed will not emit noise.

Based on the above findings of fact, the Town Planner finds the standards of this section have been met.

## K. Storage of Materials

- (1) Exposed nonresidential storage areas, exposed machinery, and areas used for the storage or collection of discarded automobiles, auto parts, metals or other articles of salvage or refuse must have sufficient setbacks and screening (such as a stockade fence or a dense evergreen hedge) to provide a visual buffer sufficient to minimize their impact on abutting residential uses and users of public streets.
- **(2)** All dumpsters or similar large collection receptacles for trash or other wastes must be located on level surfaces which are paved or graveled. Where the dumpster or receptacle is located in a yard which abuts a residential or institutional use or a public street, it must be screened by fencing or landscaping.
- **(3)** Where a potential safety hazard to children is likely to arise, physical screening sufficient to deter small children from entering the premises must be provided and maintained in good condition.

There is no proposed outdoor storage of materials.

Based on the above findings of fact, the Town Planner finds the standards of this section have been met.

**L. Capacity of the Applicant:** The applicant must demonstrate that he / she has the financial and technical capacity to carry out the project in accordance with this ordinance and the approved plan.

**<u>Technical Ability:</u>** The applicant has retained Stephen Blatt Architects to prepare the site plan.

**Financial Capacity:** The purchase of the shed will be from existing funds.

Based on the above findings of fact, the Town Planner finds the standards of this section have been met.

#### M. Design and Performance Standards

- (1) Route 100 Design Standards
- (2) Route 1 Design Standards
- (3) Town Center District Design and Performance Standards
- (4) Village Mixed Use Performance Standards.

None of the above are applicable to this project.

#### **Condition of Approval:**

1. That a building permit be issued by the CEO prior to the placement of the shed.